

DECLARATION OF PERFORMANCES

DECLARATION OF PERFORMANCE NO.

No. PTRL-DoP/MW/15/73
PETRAVENT-WV d = 30-250 mm

UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE

PETRAVENT-WV MW-EN13162-T5-DS(70,90)-CS(10)0,5-WS-WL(P)-MU1

INTENDED USE OR USES

Factory made mineral wool (MW) products for thermal insulation of buildings.

PRODUCER

Head Office		Factory	
Name:	PETRALANA S.A.	Name:	PETRALANA S.A.
Address:	Str. Mazowiecka 11 40-732 Katowice, Poland	Address:	Str. Konstytucji 74 41-905 Bytom, Poland
Phone:	+48 32 209 01 27	Phone:	+48 32 770 05 00

SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE

System 1 and System 3

HARMONIZED STANDARD

EN 13162:2012+A1:2015 „Thermal insulation products for buildings – Factory made mineral wool (MW) products - Specification”

NOTIFIED CERTIFICATION BODY OR BODIES

Instytut Mechanizacji Budownictwa i Górnictwa Skalnego nr 1454

DECLARATION OF PERFORMANCES

DECLARED CHARACTERISTICS

ESSENTIAL CHARACTERISTICS	REQUIREMENT CLAUSES IN THIS EUROPEAN STANDARD	SYMBOL	DECLARED LEVEL AND/OR CLASSES	UNIT
Reaction to fire Euroclass characteristics	Reaction to fire	RtF	A1	Euroclass
Release of dangerous substances to the indoor	Release of dangerous substances	-	NPD	-
Acoustic absorption index	Sound absorption	α_{PI} (API) i α_{WI} (AWI)	NPD	-
Impact noise transmission index	Dynamic stiffness	s' SD	NPD	MN/m ³
	Thickness, dL	dL	30-250	mm
	Compressibility, c	CP	NPD	mm
	Air flow resistivity	AFr	NPD	kPa.s/m ²
Direct airborne sound insulation index	Air flow resistivity	AFr	NPD	kPa.s/m ²
Continuous glowing combustion	Continuous glowing combustion	-	NPD	-
Thermal resistance	Thermal resistance and thermal conductivity	R	Table-Thermal Resistance	m ² K/W
		λ	0,035	W/mK
Water permeability	Short time water absorption	WS	<1	kg/m ²
Water vapour permeability	Water vapour transmission	MU	MU1	-
Compressive strength	Compressive stress or compressive strength	CS(10/Y)	0,5	kPa
	Point load	PL	NPD	-
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	Reaction to fire	A1	Euroclass
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity	Declared λ	0,035	W/mK
	Dimensional stability under specified temperature	DS	<1	%
	Dimensional stability under specified temperature and humidity conditions		<1	%
Tensile/Flexural strength	Tensile strength perpendicular to faces	TR	NPD	kPa
Durability of compressive strength against ageing/degradation	Compressive creep	CC(i1/i2/y) δ c	NPD	mm

THERMAL RESISTANCE R_D

d [mm]	30	40	50	90	100	110	120	150	160	190	200	210	220	230	240	250	
R _D [m ² K/W]	0,85	1,10	1,40	2,55	2,85	3,10	3,40	4,25	4,55	5,40	5,70	6,00	6,25	6,55	6,85	7,10	

The performance of the product identified above is in conformity with the declared performance. This declaration of performance is issued with respect to Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

PRESIDENT OF THE BOARD

PREZES ZARZĄDU
PETRALANA S.A.

Radostaw Tumielewicz

Signature

Date: 03/02/2017